

Material Safety Data Sheet

CS: 1.4.93

Page: 1 of 6

Infosafe No™ LPV5J	Issue Date : February 2011	ISSUED by SPECOTHO
--------------------	----------------------------	--------------------

Product Name : **PJ1VHT ENGINE ENAMEL**

Classified as hazardous according to criteria of NOHSC

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name	PJ1VHT ENGINE ENAMEL	
Product Code	SP1202 TO SP121, SP123 TO SP125, SP128, SP130	
Company Name	SPECO THOMAS PTY. LTD. (ABN 58 005 669 269)	
Address	1B LEVANSWELL ROAD MOORABBIN VIC 3189 Australia	
Telephone/Fax	Tel: 03 95557244	
Number	Fax: 03 95532841	
Recommended Use	Aerosol coating	
Other Names	<u>Name</u>	<u>Product Code</u>
	PJ1VHT ENGINE ENAMEL	SP133 TO SP136, SP138 TO SP142, SP756, SP758
	VHT ENGINE ENAMEL	SP120, SP755, SP760, SP758
	VHT ENGINE ENAMEL	SP119, SP120, SP754, SP755, SP760, SP761
	VHT, ENGINE ENAMEL, KERMIT GR.	SP760
	VHT "NU-CAST" CAST COATING	SP995, SP997
	VHT, HOOD BUMPER&TRIM PAINT	SP27
	VHT METAL TINTS	SP231 TO SP233
	VHT POLYURETHANE PAINTS	SP181 TO SP188
	VHT SATIN BLACK	SP906
	VHT GLOSS BLACK BARREL PAINT	SP905
	VHT "EPOXY PLUS" ROLL BAR&CHASSIS COATINGS	SP670 GLOSS BLACK
	VHT EPOXY ALL WEATHER PAINTS	SP650 TO SP668
	VHT, BRAKE CALIPER, DRUM&ROTOR PAINT	SP731 TO SP735, SP737 TO SP739
	VHT BLACK OXIDE CASE PAINT	SP903

2. HAZARDS IDENTIFICATION

Hazard Classification	Classified as hazardous according to criteria of NOHSC HAZARDOUS SUBSTANCE. DANGEROUS GOODS. Hazard classification according to the criteria of NOHSC. Dangerous goods classification according to the Australia Dangerous Goods Code.
Risk Phrase(s)	Classified as hazardous according to criteria of NOHSC R12 Extremely Flammable. R36 Irritating to eyes. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R63 Possible risk of harm to the unborn child. R66 Repeated exposure may cause skin dryness and cracking. R67 Vapours may cause drowsiness and dizziness
Safety Phrase(s)	S16 Keep away from sources of ignition - No smoking. S23 Do not breathe gas/fumes/vapour/spray S33 Take precautionary measures against static discharges. S35 This material and its container must be disposed of in a safe way. S36/37/39 Wear suitable protective clothing, gloves and eye/face protection. S51 Use only in well ventilated areas. S53 Avoid exposure - obtain special instructions before use.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Material Safety Data Sheet

CS: 1.4.93

Page: 2 of 6

Infosafe No™ LPV5J	Issue Date : February 2011	ISSUED by SPECOTH0
--------------------	----------------------------	--------------------

Product Name : **PJ1VHT ENGINE ENAMEL**

Classified as hazardous according to criteria of NOHSC

Composition, information on ingredients The classification as a carcinogen or mutagen does not apply since the substance contains less than 0.1% w/w benzene (EINECS no 200-753-7).

Ingredients	Name	CAS	Proportion
	Acetone	67-64-1	30-60 %
	Petroleum gases, liquefied	68476-85-7	30-60 %
	Solvent naphtha (petroleum), light aliph.	64742-89-8	1-10 %
	Toluene	108-88-3	1-10 %
	Ingredients determined not to be hazardous.		Balance
	2-Butoxyethanol	111-76-2	1-5 %

4. FIRST AID MEASURES

Inhalation	If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist seek medical attention.
Ingestion	Unlikely due to form of the product. If ingestion occurs, do not induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.
Skin	Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.
Eye	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eye wash and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126) or a doctor at once.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Use carbon dioxide, dry chemical, foam, water fog or water mist.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide and unidentified organic compounds.
Specific Hazards	This product is extremely flammable. Vapours are heavier than air and will 'travel' to low-level areas e.g. sumps, drains, etc. Aerosol containers may explode and may become a projectile in a fire. Keep storage tanks, pipelines, fire-exposed surfaces etc cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
Hazchem Code	2YE
Precautions in connection with Fire	Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.
Unsuitable Extinguishing Media	Do not use water jet.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
-----------------------------	---

Material Safety Data Sheet

CS: 1.4.93

Page: 3 of 6

Infosafe No™ LPV5J	Issue Date : February 2011	ISSUED by SPECOTH0
--------------------	----------------------------	--------------------

Product Name : **PJ1VHT ENGINE ENAMEL**

Classified as hazardous according to criteria of NOHSC

Undamaged cans should be gathered and stowed safely. Place inert, non-combustible absorbent material onto liquid spillage. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water authorities and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Wear appropriate protective clothing and equipment to prevent inhalation, skin and eye exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Keep containers closed when not in use. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Vapour is heavier than air and will tend to accumulate in hollows or sumps. DO NOT enter confined spaces where vapours may have collected. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for Safe Storage

Store in a cool (<49°C), dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Protect container against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. For information on the design of the storeroom, reference should be made to Australian Standard AS 2278-2000 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive. Reference should also be made to all Local, State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards

No exposure value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC), Australia. However, the available exposure limits for ingredients are listed below:

National Occupational Health And Safety Commission (NOHSC), Australia Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Oil mist	-	5	-	-	-
Acetone	500	1185	1000	2375	-
Petroleum gases, liquefied.	1000	1800	-	-	-
Toluene	50	191	150	574	Sk
2-Butoxy ethanol	20	96.9	50	242	Sk

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur. Biological Exposure Indices BEI from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:

Biological Limit Values

Determinant Indices (BEI)	Sampling Time	Biological Exposure
TOLUENE [108-88-3]		
o-Cresol in urine	End of shift	0.5mg/L
Hippuric acid in urine	End of shift	1.6g/g creatinine

Material Safety Data Sheet

CS: 1.4.93

Page: 4 of 6

Infosafe No™ LPV5J	Issue Date : February 2011	ISSUED by SPECOTHO
--------------------	----------------------------	--------------------

Product Name : **PJ1VHT ENGINE ENAMEL**

Classified as hazardous according to criteria of NOHSC

	Toluene in blood	Prior to last shift of work week	0.05mg/L
	ACETONE [67-64-1]	End of shift	50 mg/L
	Acetone in urine		
	2-BUTOXYETHANOL [111-76-2]	End of shift	200 mg/g
	creatinine		
	Butoxyacetic acid		
	BAA in urine		
Engineering Controls	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required.		
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.		
Eye Protection	Safety glasses with side shields or goggles as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.		
Hand Protection	Wear gloves of impervious material such as neoprene gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.		
Body Protection	Suitable protective clothing should be worn e.g. cotton overalls buttoned at neck and wrist. When large quantities are handled the use of chemical resistant apron and safety boots is recommended.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Aerosol paint
Odour	Solvent odour
Melting Point	Not available
Boiling Point	-25 to 199°C
Solubility in Water	Not available
Specific Gravity	Not available
pH Value	Not applicable
Vapour Pressure	52 +/- 5 psig at 21°C
Vapour Density (Air=1)	Heavier than air.
Evaporation Rate	Faster than ether
Flash Point	Propellant below -18°C
Flammability	Extremely flammable.
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	0.9%
Flammable Limits - Upper	9.5%

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions of storage and handling.
---------------------------	---

Material Safety Data Sheet

CS: 1.4.93

Page: 5 of 6

Infosafe No™ LPV5J	Issue Date : February 2011	ISSUED by SPECOTH0
--------------------	----------------------------	--------------------

Product Name : **PJ1VHT ENGINE ENAMEL**

Classified as hazardous according to criteria of NOHSC

Conditions to Avoid	Heat, direct sunlight, open flames or other sources of ignition.
Incompatible Materials	Strong oxidising agents, strong acids and bases, selected amines.
Hazardous Decomposition Products	Thermal decomposition and combustion produce noxious fumes containing carbon monoxide, carbon dioxide and unidentified organic compounds.
Hazardous Reactions	Reacts with incompatibles.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	No data available for this material.
Inhalation	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system. Vapours may cause drowsiness and dizziness.
Ingestion	Unlikely to occur due to physical state of the product. However, if ingested, may irritate the gastric tract causing nausea and vomiting.
Skin	May be irritating to skin. The symptoms may include redness, itching and swelling.
Eye	Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Chronic Effects	Harmful: danger of serious damage to health by prolonged exposure through inhalation. Repeated exposure may cause skin dryness and cracking. Prolonged or repeated skin contact may cause defatting leading to drying and cracking of skin and dermatitis. Prolonged inhalation may cause central nervous system depression with symptoms including dizziness, drowsiness, nausea and headaches. Chronic exposure may have adverse effects on the central nervous system, liver and kidneys.
Reproductive Toxicity	Possible risk of harm to the unborn child. This product is classified by NOHSC as Toxic to reproduction Category 3 : - substances that cause concern for humans owing to possible developmental toxicity effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No ecological data are available for this material.
Persistence / Degradability	No data available for this specific product.
Mobility	No data available for this specific product.
Environ. Protection	Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	Dispose of waste according to applicable local and national regulations. Do not cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature.
--------------------------------	--

14. TRANSPORT INFORMATION

Transport Information	This material is classified as a Division 2.1 (Flammable Gases) Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road or Rail. (7th edition) Division 2.1 Dangerous Goods are incompatible in a placard load with any of the following: - Class 1, Explosives - Division 2.2 Non-flammable, Non toxic gas that have a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity. - Class 3, Flammable Liquids, if both the Division 2.1 and Class 3 dangerous goods are in tanks or other receptacles with a capacity individually exceeding 500L. - Division 4.1, Flammable Solids
------------------------------	---

Material Safety Data Sheet

CS: 1.4.93

Page: 6 of 6

Infosafe No™ LPV5J	Issue Date : February 2011	ISSUED by SPECOTHO
--------------------	----------------------------	--------------------

Product Name : **PJ1VHT ENGINE ENAMEL**

Classified as hazardous according to criteria of NOHSC

	- Division 4.2, Spontaneously Combustible Substances
	- Division 4.3, Dangerous When Wet Substances
	- Division 5.1, Oxidising Agents
	- Division 5.2, Organic Peroxides
	- Class 7, Radioactive Substances
U.N. Number	1950

Proper Shipping AEROSOLS

Name

DG Class 2.1

Hazchem Code 2YE

EPG Number 2D1

IERG Number 49

15. REGULATORY INFORMATION

Regulatory Information	Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Poisons Schedule	Not Scheduled
Hazard Category	Harmful, Irritant, Extremely Flammable

16. OTHER INFORMATION

Date of preparation or last revision of MSDS	MSDS Reviewed: February 2011 Supersedes: February 2006 ...End Of MSDS...
---	--

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.